



RODACO R1

Reliable 2-layer resilient tire at an affordable price

2-LAYER NATURAL RUBBER CONSTRUCTION

- Maximizes stability
- Steel beads prevent rim slip

WIDE AND DEEP LUG PATTERN

- Ensures good traction and braking performance
- Increases tire life



PRODUCT SPECIFICATIONS



SIZE	RIM SIZE	PID		OVERALL		LOAD CAPACITY kg [lbs]					
						COUNTER BALANCED FORKLIFT TRUCKS			OTHER VEHICLES		
		NORMAL HEEL	QUICK HEEL	DIAMETER mm [in.]	WIDTH mm [in.]	UP TO 25 km/h [16 mph]		UP TO 6 km/h [4 mph]	UP TO 10 km/h [6 mph]	UP TO 25 km/h [16 mph]	STATIC
						LOAD WHEEL	STEERING WHEEL				
15 X 4 1/2 - 8	3.00D-8	9.149.15263	9.1392.15367	377	116	1040	800	1040	945	800	1210
				14.8	4.6	2295	1765	2295	2085	1765	2670
5.00 - 8	3.00D-8	9.315.15273	9.1398.15379	451	122	1415	1090	1415	1285	1090	1645
				17.8	4.8	3120	2405	3120	2835	2405	3625
16 X 6 - 8	4.33R-8	9.349.15277	9.1400.15383	408	155	1495	1150	1495	1360	1150	1735
				16.1	6.1	3295	2535	3295	3000	2535	3825
18 X 7 - 8	4.33R-8	9.359.155279	9.1401.15385	448	150	2145	1650	2145	1945	1650	2490
				17.7	5.9	4730	3640	4730	4290	3640	5490
140 / 55 - 9	4.00E - 9	-	9.754.15327	368	130	1170	900	1170	1060	900	1360
				14.5	5.1	2580	1985	2580	2335	1985	3000
6.00 - 9	4.00E - 9	9.337.15275	9.1399.15381	517	138	1885	1450	1885	1710	1450	2190
				20.4	5.4	4155	3195	4155	3770	3195	4830
21 X 8 - 9	6.00E - 9	9.370.15281	9.1402.15387	515	185	2755	2120	2755	2500	2120	3200
				20.3	7.3	6075	4675	6075	5510	4675	7055
6.50 - 10	5.00F-10	9.7.15253	9.1389.15361	564	162	2340	1800	2340	2125	1800	2720
				22.2	6.4	5160	3970	5160	4685	3970	5995
200 / 50 - 10	6.50F-10	-	9.246.15271	451	193	2470	1900	2470	2240	1900	2870
				17.8	7.6	5445	4190	5445	4940	4190	6325
23 X 9 - 10	6.50F-10	9.170.15265	9.1393.15369	580	207	3445	2650	3445	3125	2650	4000
				22.8	8.1	7595	5840	7595	6890	5840	8820
7.00 - 12	5.00S-12	9.33.15255	9.1390.15363	652	165	2920	2240	2920	2645	2240	3380
				25.7	6.5	6435	4940	6435	5830	4940	7450
23 X 10 - 12	8.00G-12	9.676.15301	9.677.15305	587	226	3770	2900	3770	3420	2900	4380
				23.1	8.9	8310	6395	8310	7540	6395	9655
27 X 10 - 12	8.00G-12	-	9.1394.15371	669	238	3900	3000	3900	3540	3000	4530
				26.3	9.4	8600	6615	8600	7805	6615	9985
5.50 - 15	4.50E-15SDC	9.45.15257	-	665	154	2430	1870	2430	2205	1870	2825
				26.2	6.1	5355	4125	5355	4860	4125	6230
7.00 - 15	5.50-15	9.49.15259	9.1430.15647	725	179	3545	2725	3545	3215	2725	4115
				28.5	7.0	7815	6010	7815	7090	6010	9070
8.25 - 15	5.50-15	9.77.15261	9.1391.15365	816	217	4615	3550	4615	4190	3550	5360
				32.1	8.5	10175	7825	10175	9235	7825	11815
28 X 9 - 15	7.00-15	9.200.15267	9.1395.15373	688	218	3900	3000	3900	3540	3000	4530
				27.1	8.6	8600	6615	8600	7805	6615	9985
250 - 15	7.00-15	9.1403.15389	9.1404.15391	709	233	4745	3650	4745	4310	3650	5510
				27.9	9.2	10460	8045	10460	9500	8045	12145
300 - 15	8.00-15	9.237.15269	9.1396.15375	807	265	5850	4500	5850	5310	4500	6795
				31.8	10.4	12895	9920	12895	11705	9920	14980
355 / 65 - 15	9.75-15	-	9.1397.15377	810	297	7800	6000	7000	6430	5450	9060
				31.9	11.7	17195	13230	15430	14175	12015	19975