



RODACO R2

High quality 3-layer resilient tire with excellent value

3-LAYER NATURAL RUBBER CONSTRUCTION

- Improves wear rate and ride quality with low heat build-up

WIDE FLAT PROFILE

- Maximizes life and traction
- Increases stability
- Lowers vibration



ALSO AVAILABLE IN
NON-MARKING COMPOUND



PRODUCT SPECIFICATIONS



SIZE	RIM SIZE	PID				OVERALL		LOAD CAPACITY kg [lbs]					
		BLACK		NON MARKING		DIAMETER mm [in.]	WIDTH mm [in.]	COUNTER BALANCED FORKLIFT TRUCKS		OTHER VEHICLES			
		NORMAL HEEL	QUICK HEEL	NORMAL HEEL	QUICK HEEL			UP TO 25 km/h [16 mph]		UP TO 6 km/h [4 mph]	UP TO 10 km/h [6 mph]	UP TO 25 km/h [16 mph]	STATIC
								LOAD WHEEL	STEERING WHEEL				
15 X 4 1/2 - 8	3.00D-8	9.921.15223	9.922.15225	9.921.15329	9.922.15331	378	108	1040	800	1040	945	800	1210
						14.9	4.3	2295	1765	2295	2085	1765	2670
5.00 - 8	3.00D-8	9.694.15007	9.695.15215	9.694.15315	9.695.15317	458	143	1415	1090	1415	1285	1090	1645
						18.5	5.6	3120	2405	3120	2835	2405	3625
16 X 6 - 8	4.33R-8	9.933.15235	9.934.15237	9.933.15343	9.934.15345	408	146	1495	1150	1495	1360	1150	1735
						16.1	5.7	3295	2535	3295	3000	2535	3825
18 X 7 - 8	4.33R-8	9.935.15013	9.936.15239	9.935.15347	9.936.15349	454	147	2145	1650	2145	1945	1650	2490
						17.9	5.8	4730	3640	4730	4290	3640	5490
140 / 55 - 9	4.00E - 9	-	9.1624.18252	-	9.1624.18270	372	130	1170	900	1170	1060	900	1360
						14.6	5.1	2580	1985	2580	2335	1985	3000
6.00 - 9	4.00E-9	9.696.15009	9.697.15217	9.696.15319	9.697.15321	522	144	1885	1450	1885	1710	1450	2190
						20.6	5.7	4155	3195	4155	3770	3195	4830
21 X 8 - 9	6.00E-9	9.702.15219	9.703.15221	9.702.15323	9.703.15325	526	185	2755	2120	2755	2500	2120	3200
						20.7	7.3	6075	4675	6075	5510	4675	7055
6.50 - 10	5.00F-10	9.660.14999	9.661.15203	9.660.15287	9.661.15289	572	157	2340	1800	2340	2125	1800	2720
						22.5	6.2	5160	3970	5160	4685	3970	5995
200 / 50 - 10	6.50F-10	-	9.1385.15241	-	9.1385.15353	456	190	2470	1900	2470	2240	1900	2870
						18.0	7.5	5445	4190	5445	4940	4190	6325
23 X 9 - 10	6.50F-10	9.923.15227	9.924.15229	9.923.15333	9.924.15335	577	212	3445	2650	3445	3125	2650	4000
						22.7	8.3	7595	5840	7595	6890	5840	8820
7.00 - 12	5.00S-12	9.659.14997	9.662.15205	9.659.15285	9.662.15291	653	169	2920	2240	2920	2645	2240	3380
						25.7	6.7	6435	4940	6435	5830	4940	7450
23 X 10 - 12	8.00G-12	9.676.15395	9.677.15209	9.676.15303	9.677.15307	585	230	3770	2900	3770	3420	2900	4380
						23.0	9.1	8310	6395	8310	7540	6395	9655
27 X 10 - 12	8.00G-12	-	9.926.15231	-	9.926.15337	671	234	3900	3000	3900	3540	3000	4530
						26.4	9.2	8600	6615	8600	7805	6615	9985
5.50 - 15	4.50E-15SDC	9.1386.15243	-	9.1386.15355	-	665	152	2430	1870	2430	2205	1870	2825
						26.2	6.0	5355	4125	5355	4860	4125	6230
7.00 - 15	5.50-15	9.663.15001	9.664.15393	9.663.15293	9.664.15295	725	179	3545	2725	3545	3215	2725	4115
						28.5	7.0	7815	6010	7815	7090	6010	9070
8.25 - 15	6.00-15	9.1625.18260	9.1626.18262	-	-	725	179	3545	2725	3545	3215	2725	4115
						28.5	7.0	7815	6010	7815	7090	6010	9070
28 X 9 - 15	5.50-15	9.665.15003	9.666.15207	-	9.666.15299	803	203	4615	3550	4615	4190	3550	5360
						31.6	8.0	10175	7825	10175	9235	7825	11815
250 - 15	7.00-15	9.680.15005	9.681.15211	9.680.15309	9.681.15311	685	208	3900	3000	3900	3540	3000	4530
						27.0	8.2	8600	6615	8600	7805	6615	9985
300 - 15	7.00-15	9.1310.15015	9.1388.15247	-	9.1388.15359	709	214	4745	3650	4745	4310	3650	5510
						27.9	8.4	10460	8045	10460	9500	8045	12145
355 / 65 - 15	8.00-15	9.929.15011	9.930.15233	-	9.930.15341	825	254	5850	4500	5850	5310	4500	6795
						32.5	10.0	12895	9920	12895	11705	9920	14980
10.00 - 20	9.75-15	-	9.1622.18248	-	9.1622.18268	821	307	7800	6000	7000	6430	5450	9060
						32.3	12.1	17195	13230	15430	14175	12015	19975
12.00 - 20	7.50-20	9.667.18238	-	-	-	1028	255	6000	5000	6000	5450	5000	7550
						40.5	10.0	13230	11025	13230	12015	11025	16645
12.00 - 20	8.00-20	9.669.18240	-	-	-	1028	255	6000	5000	6000	5450	5000	7550
						40.5	10.0	13230	11025	13230	12015	11025	16645
12.00 - 20	8.00-20	9.671.18242	-	-	-	1090	285	7560	6300	7560	6865	6300	9515
						42.9	11.2	16665	13890	16665	15135	13890	20975
12.00 - 20	8.50-20	9.1620.18244	-	-	-	1090	285	7560	6300	7560	6865	6300	9515
						42.9	11.2	16665	13890	16665	15135	13890	20975