



QUALITY TYRES
AT A GREAT PRICE



RODACO R1

Quality tyre at an affordable price

2 LAYER NATURAL RUBBER CONSTRUCTION

- Maximizes stability
- Steel beads prevent rim slip

WIDE AND DEEP LUG PATTERN

- Provides good traction and braking performance
- Long tyre life



PART NO	DESCRIPTION	TIRE SIZE	BRAND/ PRODUCT NAME	TREAD PATTERN	ACTUAL TIRE DIMENSION		LOAD CAPACITY (kg)					
							COUNTERBALANCED LIFT TRUCKS		OTHER VEHICLES			STATIC
					OVERAL DIAMETER (mm)	OVERAL WIDTH (mm)	LOAD WHEEL up to 25 km/h	STEERING WHEEL up to 25 km/h	UP TO 10 km/h	UP TO 16 km/h	UP TO 25 km/h	0 km/h
9.359.15279	18 X 7 - 8 / 4.33 AT RODACO R1 STANDARD	18 X 7 - 8	RODACO R1	AT	449	150	2145	1650	2145	1945	1650	2490
9.1403.15389	250 - 15 / 7.00 AT RODACO R1 STANDARD	250 - 15	RODACO R1	AT	709	233	4745	3650	4745	4310	3650	5510
9.200.15267	28 X 9 - 15 / 7.00 AT RODACO R1 STANDARD	28 X 9 - 15	RODACO R1	AT	688	218	3770	2900	3770	3420	2900	4380
9.237.15269	300 - 15 / 8.00 AT RODACO R1 STANDARD	300 - 15	RODACO R1	AT	807	265	5850	4500	5850	5310	4500	6795
9.315.15273	5.00 - 8 / 3.00 AT RODACO R1 STANDARD	5.00 - 8	RODACO R1	AT	451	122	1415	1090	1415	1285	1090	1645
9.337.15275	6.00 - 9 / 4.00 AT RODACO R1 STANDARD	6.00 - 9	RODACO R1	AT	517	138	1885	1450	1885	1710	1450	2190
9.7.15253	6.50 - 10 / 5.00 AT RODACO R1 STANDARD	6.50 - 10	RODACO R1	AT	564	162	2340	1800	2340	2125	1800	2720
9.33.15255	7.00 - 12 / 5.00 AT RODACO R1 STANDARD	7.00 - 12	RODACO R1	AT	652	165	2920	2240	2920	2645	2240	3380
9.49.15259	7.00 - 15 / 5.50 AT RODACO R1 STANDARD	7.00 - 15	RODACO R1	AT	725	179	3545	2725	3545	3215	2725	4115
9.77.15261	8.25 - 15 / 6.50 AT RODACO R1 STANDARD	8.25 - 15	RODACO R1	AT	816	217	4615	3550	4615	4190	3550	5360

RODACO R2

Great performance and excellent value

3 LAYER NATURAL RUBBER CONSTRUCTION

- Improves wear rate and ride quality with low heat build-up

WIDE FLAT PROFILE

- Maximizes life and traction
- Increased stability
- Low vibration tread pattern



PART NO	DESCRIPTION	TIRE SIZE	BRAND/ PRODUCT NAME	TREAD PATTERN	ACTUAL TIRE DIMENSION		LOAD CAPACITY [kg]					
							COUNTERBALANCED LIFT TRUCKS		OTHER VEHICLES			STATIC
					OVERAL DIAMETER [mm]	OVERAL WIDTH [mm]	LOAD WHEEL up to 25 km/h	STEERING WHEEL up to 25 km/h	UP TO 10 km/h	UP TO 16 km/h	UP TO 25 km/h	0 km/h
9.935.15013	18 X 7 - 8 / 4.33 TR RODACO R2 STANDARD	18 X 7 - 8	RODACO R2	TR	454	147	2145	1650	2145	1945	1650	2490
9.1310.15015	250 - 15 / 7.00 TR RODACO R2 STANDARD	250 - 15	RODACO R2	TR	709	214	4745	3650	4745	4310	3650	5510
9.680.15005	28 X 9 - 15 / 7.00 TR RODACO R2 STANDARD	28 X 9 - 15	RODACO R2	TR	685	208	3770	2900	3770	3420	2900	4380
9.929.15011	300 - 15 / 8.00 TR RODACO R2 STANDARD	300 - 15	RODACO R2	TR	825	254	5850	4500	5850	5310	4500	6795
9.694.15007	5.00 - 8 / 3.00 TR RODACO R2 STANDARD	5.00 - 8	RODACO R2	TR	458	143	1415	1090	1415	1285	1090	1645
9.696.15009	6.00 - 9 / 4.00 TR RODACO R2 STANDARD	6.00 - 9	RODACO R2	TR	522	144	1885	1450	1885	1710	1450	2190
9.660.14999	6.50 - 10 / 5.00 TR RODACO R2 STANDARD	6.50 - 10	RODACO R2	TR	572	157	2340	1800	2340	2125	1800	2720
9.659.14997	7.00 - 12 / 5.00 TR RODACO R2 STANDARD	7.00 - 12	RODACO R2	TR	653	169	2920	2240	2920	2645	2240	3380
9.663.15001	7.00 - 15 / 5.50 TR RODACO R2 STANDARD	7.00 - 15	RODACO R2	TR	725	179	3545	2725	3545	3215	2725	4115
9.665.15003	8.25 - 15 / 6.50 TR RODACO R2 STANDARD	8.25 - 15	RODACO R2	TR	803	203	4615	3550	4615	4190	3550	5360

